







Capstone® Shield ANSI • CE • CSA •

Fully adjustable elastic band // Fits over prescription glasses // Lens is coated to prevent fogging // GG504DTSHIELD goggle has a dual pane lens // Soft vinyl goggle body conforms to facial contours // Goggles pass D3: Droplet and Splash Test // Goggles pass D4: Dust Test // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Goggle combined with removable shield provides full face protection // Four ventilation holes provide airflow // Ratchet shield allows user to open or close in three positions for adjustment // Polycarbonate shield conforms to the face offering increased impact and dust protection

Lens and Shield | 5 Variations

	GG504TSHIELD •••	Clear H2X AF
	GG504DTSHIELD •	Clear Dual Pane H2X AF
	GG504TSHIELDIR3 ••	3.0 IR Filter H2X AF
	GG504TSHIELDIR5 ••	5.0 IR Filter H2X AF
	GG524TSHIELD ••	Gray H2X AF

 Fits over most prescription glasses.

Only the goggles for GG504TSHIELDIR3 and GG504TSHIELDIR5 contain IR dye. Due to the nature of the vented holes, the shield is only green tinted and does not contain the IR resin.



Capstone Face Shield and Strap

CAPSHIELD

Ratcheting shield includes strap and clips allowing the user to add to either of the Capstone 500 Series goggles // Sold as a replacement shield for GG504TSHIELD and GG504DTSHIELD



Disposable Capstone Shield Visors

VPACK6

Pack of 6 clear disposable, tear-off visors, suitable for high dust or muddy working environments



Capstone[®] Shield

SPECIFICATIONS

Capstone Shield – Goggle

Weight: 132 gm
 PD: 68 mm
 Bridge: 45 mm
 Lens base: 5.5 curve
 Lens size diagonal: 154 mm
 Lens size vertical: 78 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 91 mm
 Overall width (hinge - hinge): 180 mm
 Strap length: 232 – 365 mm

Capstone Shield – Shield

Weight: 78 gm
 Shield size: 195.58 mm x 177.64 mm
 Shield thickness: 2.0 mm

Capstone Shield – Visor

Weight: 2.4 gm
 Visor size: 32.4 mm x 6.9 mm
 Visor thickness: 0.1 mm
 Bridge: 3.3 mm

MATERIALS

Capstone Shield – Goggle

Lens: polycarbonate
 Body: polycarbonate & polyvinyl chloride (PVC)
 Nosepiece: polyvinyl chloride (PVC)
 Hinge: polycarbonate (PC) & nylon
 Strap: polyester
 Quick release: polyoxymethylene (POM)

Capstone Shield – Shield

Shield: polycarbonate
 Holder: polycarbonate
 Strap: polyester

Capstone Shield – Visor

Visor: polyethylene terephthalate (PET)

MARKINGS

Part No.	Lens Marking	Frame Marking	Shield Marking
GG504TSHIELD	PZ87+U6	PZ87 + D3 / P c SEI CAN/CSA Z94.3-15	PZ87 + / P c SEI CAN/CSA Z94.3-15
GG504DTSHIELD	PZ87+U6 L1.3	PZ87 + D3 / P c SEI CAN/CSA Z94.3-15	PZ87 + / P c SEI CAN/CSA Z94.3-15
GG504TSHIELDIR3	PZ87+W3	PZ87 + D3	PZ87 +
GG504TSHIELDIR5	PZ87+W5	PZ87 + D3	PZ87 +
GG524TSHIELD	PZ87+U6 L2.5	PZ87 + D3 / P c SEI CAN/CSA Z94.3-15	PZ87 + / P c SEI CAN/CSA Z94.3-15
CAPSHIELD	–	–	P Z87+

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L1.3: 85% Max. Visible Light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & splash test (goggle only)
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Shield Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices