



**PYRAMEX**  
Perform At Your Peak™

**Goliath®** ANSI CE CSA AUS



CO-INJECTED  
TEMPLES



POLARIZED  
OPTION

Co-injected, rubber temples

Part No.	Black Frame
SB5610D ●●●●	Clear
SB5610DT ●●●●	AF Clear H2X
SB5620D ●●●●	Gray
SB5620DT ●●●●	AF Gray H2X
SB5621D ●●●●	Polarized Gray
SB5645D ●●●●	Ice Orange Mirror
SB5665D ●●●●	Ice Blue Mirror
SB5670D ●●●●	Silver Mirror
SB5680D ●●●●	I/O Mirror
Part No.	White Frame
SW5620D ●●●●	Gray
SW5655D ●●●●	Sky Red Mirror
SW5665D ●●●●	Ice Blue Mirror



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Australian (AS/NZS 1337) (●) standards.



## Goliath®

### General Specifications

Weight: 35 gm  
 PD: 68 mm  
 Bridge: 13.8 mm  
 Lens base: 8 curve  
 Lens size diagonal: 62.6 mm  
 Lens size vertical: 37.6 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 163.5 mm  
 Overall width (hinge - hinge): 131 mm  
 Closest point between temple tips: 96.5 mm  
 Closest point between lens: 18 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate & thermoplastic rubbers (TPR)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Side shields: polycarbonate

Part No.	Lens Markings	Frame Markings
SB5610D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5610DT	P Z87 + U6	P Z87 +
SB5620D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5620DT	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5621D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5645D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5665D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5670D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5680D	P Z87 + U6 L1.7	P Z87 +
SW5620D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SW5655D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SW5665D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Frame Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967